

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
23.07.2003 Bulletin 2003/30

(51) Int Cl.7: **H04N 7/14**

(21) Application number: **03250305.4**

(22) Date of filing: **17.01.2003**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT SE SI SK TR
Designated Extension States:
AL LT LV MK RO

(30) Priority: **17.01.2002 JP 2002008193**

(71) Applicants:
• **FUJITSU LIMITED**
Kawasaki-shi, Kanagawa 211-8588 (JP)
• **MITSUBISHI DENKI KABUSHIKI KAISHA**
Tokyo 100-8310 (JP)

(72) Inventors:
• **Taniguchi, Shigeki, c/o Fujitsu Limited**
Kawasaki-shi, Kanagawa 211-8588 (JP)


• **Yamamoto, Mitsuhiko, c/o Fujitsu Limited**
Kawasaki-shi, Kanagawa 211-8588 (JP)
• **Kikuchi, Misao, c/o Fujitsu Limited**
Kawasaki-shi, Kanagawa 211-8588 (JP)
• **Kage, Hiroshi, c/o Mitsubishi Denki KK**
Tokyo 100-8310 (JP)
• **Takeda, Akihiro, c/o Mitsubishi Denki KK**
Tokyo 100-8310 (JP)
• **Tanaka, Kenichi, c/o Mitsubishi Denki KK**
Tokyo 100-8310 (JP)

(74) Representative: **Williams, Michael Ian**
Haseltine Lake
Imperial House
15-19 Kingsway
London WC2B 6UD (GB)

(54) **Information device and computer product**

(57) A transmission-side cellular phone (20) sends, via a mail server (40), to a reception-side cellular phone (30), a face image and its attribute information as an attachment to an email. The reception-side cellular phone (30) extracts the face image from the email, selects face part images from among a plurality of face

part images stored in the face part storing section, combines the face image and the selected face parts, and displays the combined image. The reception-side cellular phone (30) selects the face part images based on, for example, a number of times a telephone call from a person was not attended in a predetermined period.



Description

[0001] The present invention relates to an information device such as a cellular phone having a function for combining images.

[0002] Portable telephone (hereinafter "cellular phone") with built-in camera has appeared in the market. This cellular phone has a possibility of being able to realize advanced communications that the cellular phones without the built-in camera have not been able to realize. As a result, it is expected that the cellular phones with built-in camera will become more popular and widely used.

[0003] The cellular phone with a built-in camera has a function for transmitting an image, for example, a photograph of a face of a person, to another cellular phone as an attachment to an email. Some cellular phones also have a function to process the image, for example, to compresses or trim the image. The original image or the processes image may be used as an idle image (i.e., an image displayed on the idle screen).

[0004] When an image of face of one person is transmitted to the other person, it is possible to convey the face or expressions on the face of the one person to the other person, and realize better communications between the users. However, since the data quantity of the image handled by the cellular phones is high, usually about 8 KB, it exerts a great burden on the communication lines, and sometimes real-timeness of the communications is lost.

[0005] Moreover, as the data quantity of the image exerts a great burden on the mail servers, some Internet providers even tend to prohibit transmission of images among the users. As a result, the users loose the opportunity to communicate with each other using images.

[0006] Furthermore, using of an illustration or an image of a face as the idle image was know even before a cellular phone with a built-in camera appeared in the market. In other words, the advantages of the built-in camera in the cellular phone have not been fully utilized.

[0007] According to one aspect of the present invention, a face image and a plurality of face part images corresponding to facial expressions are obtained; a facial expression is determined; and the face image and the face part images corresponding to the facial expression are combined to obtain a combined face image. The combined face image may be displayed on a display or transmitter to other person.

[0008] According to another aspect of the present invention, a first face image and a second face image is obtained; a method for combining is determined; and the first face image and the second face image are combined based on the method for combining to obtain a combined face image. The combined face image may be displayed on a display or transmitter to other person.

[0009] According to still another aspect of the present invention a first face image and a second face image are obtained; a similarity between the first face image

and the second face image and a relationship between the persons of the first face image and the second face image determined from the similarity are determined; and the similarity, the relationship or both the similarity and the relationship is displayed on a display.

[0010] These and other objects, features and advantages of the present invention are specifically set forth in or will become apparent from the following detailed descriptions of the invention when read in conjunction with the accompanying drawings.

Fig. 1 shows a structure of a cellular phone according to one embodiment of the present invention; Fig. 2A to Fig. 2C explain how a portrait is prepared by the cellular phone shown in Fig. 1;

Fig. 3 shows one example of a system for realizing communications using the cellular phone shown in Fig. 1;

Fig. 4 shows storage contents of a portrait storing section shown in Fig. 3;

Fig. 5 shows storage contents of a face part storing section shown in Fig. 3;

Fig. 6 shows storage contents of a call register storing section shown in Fig. 3;

Fig. 7 shows storage contents of an expression assignment information storing section shown in Fig. 3;

Fig. 8 shows an example of processes executed by a reception-side cellular phone shown in Fig. 3;

Fig. 9 shows another example of processes executed by the reception-side cellular phone shown in Fig. 3;

Fig. 10 explains how a portrait is prepared;

Fig. 11 shows another example of a system for realizing communications using the cellular phone shown in Fig. 1;

Fig. 12 shows an example of processes performed by a transmission-side cellular phone shown in Fig. 11;

Fig. 13 shows an example of processes performed by a reception-side cellular phone shown in Fig. 11; Fig. 14 shows still another example of communications performed using the cellular phone shown in Fig. 1;

Fig. 15 shows an example of processes performed by a transmission-side cellular phone shown in Fig. 14;

Fig. 16 shows still another example of communications performed using the cellular phone shown in Fig. 1;

Fig. 17 shows an example of processes performed by a transmission-side cellular phone shown in Fig. 16;

Fig. 18 shows an example of processes performed by a reception-side cellular phone shown in Fig. 16;

Fig. 19 shows a structure of a cellular phone according to another embodiment of the present invention;

Fig. 20 shows an example of processes performed

by a portrait combining section shown in Fig. 19; and

Fig. 21 shows an example of processes performed by a relationship estimator shown in Fig. 19.

[0011] Exemplary embodiments of the cellular phone according to the present invention are explained in detail below by referring to the accompanying drawings.

[0012] Fig. 1 shows a structure of a cellular phone 1, as an example of an information device, according to one embodiment of the present invention. The cellular phone 1 comprises of a camera 10, a display 11, a microphone 12, a speaker 13, an image processing section 14, a voice processing unit 15, a communications section 16, and an antenna 17.

[0013] The image processing section 14 includes a portrait preparing unit 14A. This portrait preparing unit 14A receives an image (see Fig. 2A) of a face of a person (hereinafter "face image") photographed by the camera 10, converts the image into binary data, for example, and projects the data on a two dimensional coordinate system. Based on the projected data, the image processing section 14 determines: position of the overall face (hereinafter "total face"), position of the eyes, the nose, the mouth, the hair, and the like (hereinafter "face parts") in the total face (see Fig. 28), color of the total face, and color of the hair. Finally, based on this information, the image processing section 14 prepares a portrait of the face (hereinafter "portrait") (see Fig. 2C). When preparing the portrait, a standard color is used for the total face, and another standard color is used for the hair. The portrait of desired size may be prepared. It should be noted that, any method other than using the projected data may be used to prepare the portrait.

[0014] The processed face image is then transmitted to, for example, other cellular phone via the communications section 16 and the antenna 17.

[0015] Thus, in the cellular phone 1 of the present invention, the face image obtained by the camera 10 is not transmitted as it is, but the face image is processed to obtain a portrait and the portrait is transmitted. Since the portrait is used, it is possible to realize communications between the users with a simpler and slick hardware and at an extremely high speed.

[0016] Fig. 3 shows one example of a system for realizing communications using the cellular phone shown in Fig. 1. This system comprises of a transmission-side cellular phone 20 and a reception-side cellular phone 30 connected via a mail server 40.

[0017] The transmission-side cellular phone 20 comprises of a portrait preparing section 21 that prepares a portrait and its attribute information based on the face image photographed by the camera 10, a portrait transmitting section 22 that transmits the portrait and the attribute information to the mail server 40, and a calling section 23 that makes a telephone call to the reception-side cellular phone 30. The attribute information in-

cludes the position of the total face, the positions of the face parts, the color of the total face, and the color of the hair, and the like. It is preferable that, when preparing a portrait, the portrait preparing section 21 prepares a portrait of a predetermined size.

[0018] The reception-side cellular phone 30 comprises of a portrait receiving section 31 that receives the portrait and the attribute information from the mail server 40, a portrait storing section 32 that stores the portrait and the attribute information, a face part storing section 33 that stores the face parts of the portrait prepared to change the expression of the portrait, a call register storing section 34 that stores the record of calls received (hereinafter "call reception") from the transmission-side cellular phone 20, an expression assignment information storing section 35 that stores expression assignment information that indicates to which expression the expression of the portrait is to be changed, a portrait changing section 36 that changes the portrait stored in the portrait storing section 32, a portrait output section 37 that outputs to the display 11 the changed portrait, and a call receiving section 38 that receives a call from the transmission-side cellular phone 20.

[0019] The functions of sections of the transmission-side cellular phone 20 and the reception-side cellular phone 30 may be realized by hardware or software (i. e., computer programs) or both. When the functions are realized using software, a recording medium such as a semiconductor memory may be provided to store the software.

[0020] As shown in Fig. 4, the portrait storing section 32 stores the portrait and the attribute information in correlation with the telephone number of the sender (i.e., the transmission-side cellular phone 20).

[0021] As shown in Fig. 5, the face part storing section 33 stores expressions of the face parts in correlation with condition of the expression (hereinafter "expression assignment information"). The expression assignment information is, for example, small anger, large anger, surprise, and the like.

[0022] An angry face of a person may be represented with the eyes turned upward at the outer corners, and the mouth turned down at the corners. Therefore, if the expression assignment information is anger, then a images of eyes turned upward at the outer corners, and image of mouth turned down at the corners are stored in the face part storing section 33 in correlation with the expression assignment information of "anger".

[0023] The face parts stored in the face part storing section 33 have sizes that match with the size of the portrait. The face parts with expressions may be prepared somewhere else and may be stored at the mail server 40. And, the transmission-side cellular phone 20 may be made to download the face parts.

[0024] The call register storing section 34 stores the call register information. As shown in Fig. 6, the call register information includes a telephone number of the caller, the time at which the call was received (hereinaf-

ter "call reception time"), and information that shows whether the call was attended (hereafter "absence or response").

[0025] As shown in Fig. 7, the expression assignment information storing section 35 stores number of times a call from a person was not attended (hereinafter "number of times of absence") and the expression assignment information in correlated manner.

[0026] A case is explained here in which expressions of the portrait are changed according to the number of times of absence using the flowcharts in Fig. 8 and Fig. 9. The process shown in these figures is performed by the reception-side cellular phone 30.

[0027] The transmission-side cellular phone 20 transmits a portrait and corresponding attribute information to the mail server 40 and the portrait receiving section 31 of the reception-side cellular phone 30 receives the portrait and the attribute information from the mail server 40 (step ST1). It is assumed here that the portrait is a face image of the user or owner of the transmission-side cellular phone 20. The portrait receiving section 31 of the reception-side cellular phone 30 also obtains the telephone number of the transmission-side cellular phone 20 (step ST2). Finally, the portrait, the attribute information, and the telephone number are stored in the portrait storing section 32 (step ST3).

[0028] When a call is received from the transmission-side cellular phone 20, the reception-side cellular phone 30 obtains the telephone number of the transmission-side cellular phone 20 (see step ST4 in Fig. 9). The portrait changing section 36 extracts, from the portrait storing section 32, the portrait and the attribute information relating to the telephone number obtained (step ST5). In other words, a portrait of the caller is obtained based on the telephone number.

[0029] Next, the portrait changing section 36 obtains information, from the call register storing section 34, on how many times the call from the transmission-side cellular phone 20 was not attended during a predetermined period (for example, two hours) (see step ST6). Then the portrait changing section 36 obtains expression assignment information, from the expression assignment information storing section 35, relating to the number of times the call was not attended (step ST7).

[0030] Next, the portrait changing section 36 obtains face parts with expressions relating to the expression assignment information from the face parts storing section 33 (step ST8). Then the portrait changing section 36 changes the portrait obtained via the mail server 40 by combining the face parts with expressions with the portrait (step ST9). Finally, the portrait output section 37 outputs the changed portrait to the display 11 where the portrait is displayed (step ST10).

[0031] As a result, for example, if the telephone call from a caller is second time in two hours, and the owner of the receiver has not attended the first telephone call, then a face image of the caller that is smiling is displayed on the display of the receiver. If the telephone call from

a caller is third time in two hours, and the owner of the receiver has not attended the previous two telephone calls, then a face image of the caller that is little angry is displayed on the display of the receiver. If the telephone call from a caller is fourth time in two hours, and the owner of the receiver has not attended the previous three telephone calls, then, as shown in Fig. 10, a face image of the caller that is angry is displayed on the display of the receiver. Thus, the receiver will know the feelings of the caller for not attending the previous telephone calls which realizes advanced communications between the users.

[0032] Fig. 11 shows another example of a system for realizing communications using the cellular phone shown in Fig. 1. This system comprises of a transmission-side cellular phone 20A and a reception-side cellular phone 30A connected via the mail server 40.

[0033] In the system shown in Fig. 3, the reception-side cellular phone 30 decides the expression assignment information itself based on the number of calls that have not been attended. On the other hand, in the system shown in Fig. 11, the transmission-side cellular phone 20A sends the expression assignment information to the reception-side cellular phone 30A.

[0034] The transmission-side cellular phone 20A comprises of the portrait preparing section 21 that prepares a portrait and its attribute information based on the face image photographed by the camera 10, a portrait storing section 24 that stores the portrait and the attribute information, a mail preparing section 25 that prepares a mail and attaches the portrait and the attribute information to the email, a mail transmitting section 26 that transmits the email to the mail server 40, an expression assignment information obtaining section 27 that obtains the expression assignment information through interaction with the user, and the calling section 23 that sends a call signal (i.e., makes a telephone call) to the reception-side cellular phone 30A and embeds the expression assignment information into the call signal. The attribute information includes the position of the total face, the positions of the face parts, the color of the total face, and the color of the hair, and the like. It is preferable that, when preparing a portrait, the portrait preparing section 21 prepares a portrait of a predetermined size.

[0035] The reception-side cellular phone 30A comprises a mail receiving section 39 that receives a mail with a portrait attached to it from the mail server 40, the face part storing section 33 that stores the face parts of the portrait prepared to change the expression of the portrait, the portrait changing section 36 that changes expressions of the portrait attached to the mail, the portrait output section 37 that outputs the portrait to the display 11, and the call receiving section 38 that receives a call signal with the expression assignment information embedded in it from the transmission-side cellular phone 20A. The call receiving section 38 extracts the expression assignment information embedded in the

call signal.

[0036] The functions of sections of the transmission-side cellular phone 20A and the reception-side cellular phone 30A may be realized by hardware or software (i. e., computer programs) or both. When the functions are realized using software, a recording medium such as a semiconductor memory may be provided to store the software. The face part storing section 33 stores the information shown in Fig. 5.

[0037] Same reference numerals have been attached to those sections in Fig. 3 and Fig. 11 that perform same or similar functions or have same or similar configurations.

[0038] The transmission-side cellular phone 20A performs the process shown in Fig. 12, while the reception-side cellular phone 30A performs the process shown in Fig. 13.

[0039] As shown in Fig. 12, the mail preparing section 25 of the transmission-side cellular phone 20A reads the portrait stored in the portrait storing section 24, prepares the email, and attaches the portrait to the email (step SS1). Generally, a portrait of the owner of the transmission-side cellular phone 20A is stored in the portrait storing section 24. Next, the expression assignment information obtaining section 27 obtains expression assignment information by interaction with the user or the owner of the transmission-side cellular phone 20A (step SS2).

[0040] Then, the mail transmitting section 26 transmits the email (with the portrait and the attribute information attached) to the mail server 40 (step SS3). The mail preparing section 25 may be made to embed the attribute information into the header of the email instead of attaching the attribute information.

[0041] Next, the calling section 23 transmits a call signal with the expression assignment information embedded to the reception-side cellular phone 30A (step SS4). The expression assignment information may be embedded into a header of the call signal. Thus, the reception-side cellular phone 30A comes to know that the transmission-side cellular phone 20A has sent a mail to it.

[0042] Thus, the portrait and attribute information are transmitted from the transmission-side cellular phone 20A to the reception-side cellular phone 30A in the form of an email. On the other hand, the expression assignment information is transmitted from the transmission-side cellular phone 20A to the reception-side cellular phone 30A through the call signal.

[0043] When a call signal is received by the call receiving section 38 of the reception-side cellular phone 30A, the call receiving section 38 extracts the expression assignment information embedded in the call signal (step SS5 in Fig. 13). The mail receiving section 39 receives a mail from the mail server 40 and sends the portrait and the attribute information attached to the email to the portrait changing section 36 (step SS6).

[0044] Then, the portrait changing section 36 obtains, from the face parts storing section 33, the face parts with

expressions relating to the expression assignment information (step SS7). Then the portrait changing section 36 changes the portrait obtained via the email by combining the face parts with expressions with the portrait (step ST8). Finally, the portrait output section 37 outputs the changed portrait to the display 11 where the portrait is displayed (step SS9).

[0045] As a result, for example, if the caller is in happy mood, he can select expression assignment information that will display a face image that is smiling on the display of the cellular phone of the receiver. Thus, the receiver will know the feelings of the caller which realizes advanced communications between the users.

[0046] It has been mentioned above to embed the expression assignment information into the call signal, however, the expression assignment information may be attached to an email. Moreover, the expression assignment information may be embedded into a header of the email along with the attribute information.

[0047] Fig. 14 shows still another example of a system for realizing communications using the cellular phone shown in Fig. 1. This system comprises of a transmission-side cellular phone 20B and a reception-side cellular phone 30B connected via the mail server 40.

[0048] In the system shown in Fig. 11, the transmission-side cellular phone 20A sends the expression assignment information to the reception-side cellular phone 30A and the reception-side cellular phone 30A changes the portrait of based on the expression assignment information. On the other hand, in the system shown in Fig. 14, the transmission-side cellular phone 20B changes the portrait based on the expression assignment information and sends the changed portrait to the reception-side cellular phone 30B for displaying.

[0049] The transmission-side cellular phone 20B comprises of the portrait preparing section 21 that prepares a portrait and its attribute information based on the face image photographed by the camera 10, the portrait storing section 24 that stores the portrait and the attribute information, a face part storing section 28 that stores the face parts of the portrait prepared to change the expression of the portrait, the expression assignment information obtaining section 27 that obtains the expression assignment information through interaction with the user, a portrait changing section 29 that changes the portrait, the mail preparing section 25 that prepares an email and attaches the portrait to the email, the mail transmitting section 26 that transmits the email to the reception-side cellular phone 30B via the mail server 40, and the calling section 23 that makes a telephone call to the reception-side cellular phone 30B.

[0050] The reception-side cellular phone 30B comprises of the mail receiving section 39 that receives the email from the mail server 40, the portrait output section 37 that outputs the portrait to the display 11, and the call receiving section 38 that receives a notification from the transmission-side cellular phone 20B that an email has been send to the reception-side cellular phone 30B.

[0051] The functions of sections of the transmission-side cellular phone 20B and the reception-side cellular phone 30B may be realized by hardware or software (i. e., computer programs) or both. When the functions are realized using software, a recording medium such as a semiconductor memory may be provided to store the software. The face part storing section 28 stores the information shown in Fig. 5.

[0052] Same reference numerals have been attached to those sections in Fig. 3, Fig. 11, and Fig. 14 that perform same or similar functions or have same or similar configurations.

[0053] The transmission-side cellular phone 20B performs the process shown in Fig. 15.

[0054] The portrait changing section 29 reads the portrait stored in the portrait storing section 24 (step SK1). Generally, a portrait of the owner of the transmission-side cellular phone 20B is stored in the portrait storing section 24. Next, the expression assignment information obtaining section 27 obtains the expression assignment information by interaction with the user or the owner of the transmission-side cellular phone 20B and supplies the expression assignment information to the portrait changing section 29 (step SK2).

[0055] Then, the portrait changing section 29 obtains, from the face part storing section 28, the face parts relating to the expression assignment information (step SK3). Next, the portrait changing section 29 changes the portrait by combining the face parts (step SK4).

[0056] Next, the portrait changing section 29 supplies the portrait to the mail preparing section 25, and the mail preparing section 25 prepares an email and attaches the portrait to the email (step SK5). The mail transmitting section 26 transmits the email with the portrait attached to it to the mail server 40 (step SK6). Finally, the calling section 23 sends a call signal to the reception-side cellular phone 30B to inform the reception-side cellular phone 30B that an email has been sent (step SK7).

[0057] The mail receiving section of the reception-side cellular phone 30B receives the email with the portrait attached to it from the mail server 40, extracts the portrait from the email and supplies the portrait to the portrait output section 37. Finally, the portrait output section 37 outputs the portrait to the display 11 where the portrait is displayed.

[0058] As a result, for example, if the caller is in happy mood, he can select expression assignment information so that a face image that is smiling is sent to the receiver as a mail attachment and displayed on the display of the cellular phone of the receiver. Thus, the receiver will know the feelings of the caller which realizes advanced communications between the users.

[0059] Fig. 16 shows still another example of a system for realizing communications using the cellular phone shown in Fig. 1. This system comprises of a transmission-side cellular phone 20C and a reception-side cellular phone 30C connected via the mail server 40.

[0060] In the system shown in Fig. 16, the transmis-

sion-side cellular phone 20C sends face parts relating to desired expression assignment information to the reception-side cellular phone 30C via an email and the reception-side cellular phone 30C changes the portrait of based on the expression assignment information and displays the portrait.

[0061] The transmission-side cellular phone 20C comprises of the face part storing section 28 that stores the face parts of the portrait prepared to change the expression of the portrait, the expression assignment information obtaining section 27 that obtains the expression assignment information through interaction with the user, the mail preparing section 25 that prepares an email and attaches the face parts to the email, the mail transmitting section 26 that transmits the email to the reception-side cellular phone 30C via the mail server 40, and the calling section 23 that makes a telephone call to the reception-side cellular phone 30C.

[0062] The reception-side cellular phone 30C comprises of the mail receiving section 39 that receives the email from the mail server 40, the portrait storing section 32 that stores the portrait and corresponding attribute information downloaded from the transmission-side cellular phone 20C via the mail server 40, the portrait changing section 36 that changes the portrait, the portrait output section 37 that outputs the portrait to the display 11, and the call receiving section 38 that receives a notification from the transmission-side cellular phone 20C that an email has been send to the reception-side cellular phone 30C.

[0063] The functions of sections of the transmission-side cellular phone 20C and the reception-side cellular phone 30C may be realized by hardware or software (i. e., computer programs) or both. When the functions are realized using software, a recording medium such as a semiconductor memory may be provided to store the software.

[0064] The face part storing section 28 stores the information shown in Fig. 5. Moreover, the portrait storing section 32 stores the information shown in Fig. 4.

[0065] Same reference numerals have been attached to those sections in Fig. 3, Fig. 11, Fig. 14, and Fig. 16 that perform same or similar functions or have same or similar configurations.

[0066] The transmission-side cellular phone 20C performs the process shown in Fig. 17, while the reception-side cellular phone 30C performs the process shown in Fig. 18.

[0067] As shown in Fig. 17, the expression assignment information obtaining section 27 obtains expression assignment information by interaction with the user or the owner of the transmission-side cellular phone 20C (step SA1). Then, the expression assignment information obtaining section 27 obtains face parts, from the face part storing section 28, relating to the expression assignment information and supplies the face parts to the mail preparing section 25 (step SA2). The mail preparing section 25 prepares an email and attaches the

face parts to the email (step SA3). Next, the mail transmitting section 26 transmits the email to the reception-side cellular phone 30C via the mail server 40 (step SA4). Finally, the calling section 23 sends a call signal to the reception-side cellular phone 30C to inform the reception-side cellular phone 30C that an email has been sent (step SA5).

[0068] The mail receiving section 39 of the reception-side cellular phone 30C receives the email with the face parts attached to it from the mail server 40 (step SA6) and extracts the face parts from the email (step SA7). Next, the portrait changing section 36 obtains the telephone number of the transmission-side cellular phone 20C (step SA8). Next, the portrait changing section 36 obtains, from the portrait storing section 32, the portrait and the attribute information relating to the telephone number of the transmission-side cellular phone 20C (step SA9).

[0069] Then, the portrait changing section 36 changes the portrait by combining the face parts with expressions with the portrait stored in the portrait storing section 32 (step SA10). Finally, the portrait output section 37 outputs the changed portrait to the display 11 where the portrait is displayed (step SA11).

[0070] As a result, for example, if the caller is in happy mood, he can select expression assignment information so that face parts that will display a face image that is smiling is sent to the receiver as a mail attachment. Thus, the receiver will know the feelings of the caller which realizes advanced communications between the users.

[0071] Fig. 19 shows a structure of a cellular phone 99, as an example of an information device, according to another embodiment of the present invention.

[0072] The cellular phone 99 comprises of the camera 10, the display 11, a portrait preparing section 100 that prepares a portrait and attribute information of the portrait based on the face image photographed by the camera 10, a portrait storing section 101 that stores the portrait and the attribute information, a portrait output section 102 that outputs the portrait stored in the portrait storing section 101 or the portrait prepared by the portrait preparing section 100 (hereinafter "two portraits") to the display 11, a portrait combining section 103 that combines the two portraits, and a relationship estimator 104 that estimates the relationship between the persons of the portraits based on the two portraits.

[0073] The functions of sections of the cellular phone 99 may be realized by hardware or software (i.e., computer programs) or both. When the functions are realized using software, a recording medium such as a semiconductor memory may be provided to store the software.

[0074] Fig. 20 shows an example of processes performed by the portrait combining section 103. This process starts when the user or the owner of the cellular phone 99 issues a command to start the process.

[0075] The portrait combining section 103 first selects

two portraits to be combined, through interaction with the user (step SB1). The portrait combining section 103 selects two portraits to be combined from among the portraits prepared by the portrait preparing section 100 and/or the portraits stored in the portrait storing section 101.

[0076] Next, the portrait combining section 103 selects a method for combining (hereinafter "combining method") the portraits through interaction with the user. Following methods may be considered as the methods for combining the two portraits A and B:

- (1) use the eyes and the mouth of the portrait A and use the total face and other face parts of the portrait B (hereinafter "method M1"),
- (2) based on random numbers determine which parts of the portrait A and B are to be used (hereinafter "method M2"),
- (3) use the position information of the total face and the face parts of the portrait A, use the shapes of the total face and the face parts of the portrait B (hereinafter "method M3"),
- (4) use an intermediate value of the face parts of the portrait A and B (hereinafter "method M4").

[0077] The portrait combining section 103 selects one of these combining methods through an interaction with the user. It should be noted that a combining method other than the combining methods mentioned above may be used.

[0078] Next, the portrait combining section 103 decides whether the method M1 has been selected (step SB3). If it is decided that the method M1 has been selected, the portrait combining section 103 determines from which portrait the total face is to be used and from which portrait the face parts are to be used, through interaction with the user (step SB4).

[0079] If the method M1 has not been selected at the step SB3, then it is decided whether the method M2 has been selected (step SB5). If it is decided that the method M2 has been selected, the portrait combining section 103 determines from which portrait the total face is to be used, and from which portrait each face part is to be used, by generating 1 or 2 at random (step SB6).

[0080] If the method M2 has not been selected at the step SB5, then it is decided whether the method M3 has been selected (step SB7). If it is decided that the method M3 has been selected, the portrait combining section 103 determines from which portrait the position information of the total face and the face parts is to be used, and from which portrait the shape information of the total face and the face parts is to be used, through interaction with the user (step SB8).

[0081] If the method M3 has not been selected at the step SB7, then it will mean that selected method is M4. In this case, the portrait combining section 103 calculates the intermediate value of the two shapes and the positions respectively for each of the total face and each

face part, thereby to determine the total face and each face part to be pasted to form the composite portrait (step SB9).

[0082] Finally, the portrait combining section 103 combines the parts selected at step SB4 or SB6 or SB8 or SB9 to obtain a changed portrait (step SB10). The changed portrait may be displayed on the display 11 or it may be transmitted to other person.

[0083] It is mentioned above to combine parts of two portraits to obtain a changed portrait but parts of more than two portraits may be combined to obtain two or more portraits.

[0084] Thus, according to the process shown in the flowchart of Fig. 20, parts of two different portraits can be combined as desired by the user. As a result, if, for example, portraits of a man and a woman (say husband and wife) may be combined to guess a face of would be child of the two. With this arrangement, it is possible to realize advanced communications between the users.

[0085] Fig. 21 shows an example of processes performed by the relationship estimator 104. This process starts when the user or the owner of the cellular phone 99 issues a command to start the process.

[0086] The relationship estimator 104 selects two portraits through interaction with the user (step SC1). In other words, the relationship estimator 104 selects two portraits to carry out the estimation from among the portraits prepared by the portrait preparing section 100 and the portraits stored in the portrait storing section 101.

[0087] Next, the relationship estimator 104 obtains the attribute information of the portraits (i.e., the position of the total face, the positions of the face parts, the color of the total face, and the color of the hair) from the portrait preparing section 100 and the portrait storing section 101 (step SC2).

[0088] Next, the relationship estimator 104 calculates respective feature values of the portraits based on the attribute information of the portraits (where what kinds of feature values are to be used are set in advance), and calculates values of the parameters for estimating the relationship defined by difference values and ratios of the calculated feature values (step SC3).

[0089] For example, the relationship estimator 104 calculates feature values such as a distance between the two eyes, a size of a triangle formed by the two eyes and the mouth, a distance between a straight line formed by combining the two ears and a straight line formed by combining the two eyes, sizes of the eyes, a ratio of the size of the eye to the size of the ear, and the like. Then, the relationship estimator 104 calculates values of the parameters for estimating the relationship defined by the difference values and the ratios of the calculated feature values.

[0090] Next, the relationship estimator 104 substitutes the calculated parameters into the similarity calculation expression prepared in advance, thereby to calculate the similarity between the two portraits selected to estimate the relationship (step SC4).

[0091] Next, the relationship estimator 104 specifies the relationship corresponding to the calculated similarity. For example, when the relationship is within a certain range of similarity, the two persons of the portraits selected to carry out the estimation are defined such that the portraits represent the likeness between the parent (s) and the child, represent the likeness between the brothers, represent the likeness between the cousins, or represent no likeness at all. Based on this, the relationship estimator 104 specifies the relationship between the two persons corresponding to the calculated similarity.

[0092] Finally, the relationship estimator 104 makes the display 11 display the specified relationship.

[0093] According to the flowchart shown in Fig. 21, the user can determine, for example, similarity between the portraits of two persons. With this arrangement, it is possible to realize advanced communications between the users.

[0094] Instead of outputting the relationship between the two persons in the expression form of the likeness between the parent(s) and the child, it is also possible to output the calculated similarity itself.

[0095] Although a cellular phone is taken as an example of the information device, the present invention may be realized on any other information device such as a portable computer or a personal digital assistant (PDA).

[0096] As explained above, according to the portable electronic device of the present invention, it is possible to change the expression of the portrait by using the portrait having a reduced quantity of data generated based on the face image. With this arrangement, it is possible to realize advanced communications between the users.

[0097] According to the portable electronic device of the present invention, it is possible to generate, for example, the face of a child born between Mr. A and Ms. B by using the portraits having a reduced quantity of data generated based on the face images. With this arrangement, it is possible to realize advanced communications between the users.

[0098] According to the portable electronic device of the present invention, it is possible to estimate, for example, a relationship between Mr. A and Ms. B by using the portraits having a reduced quantity of data generated based on the face images. With this arrangement, it is possible to realize advanced communications between the users.

[0099] Although the invention has been described with respect to a specific embodiment for a complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art which fairly fall within the basic teaching herein set forth.

Claims**1.** An information device comprising:

an image obtaining unit that is arranged to obtain a face image and a plurality of face part images corresponding to facial expressions; an expression determining unit that is arranged to determine a facial expression; and an image combining unit that is arranged to combine the face image and the face part images corresponding to the facial expression to obtain a combined face image.

2. The information device according to claim 1, further comprising a communications unit for transmitting the face image, the face part images, or the combined face image to another information device.**3.** The information device according to claim 1 or 2, further comprising a digital camera for acquiring the face image and the face part images, wherein the image obtaining unit is arranged to obtain the face image and the face part images acquired by the digital camera.**4.** The information device according to any of the preceding claims, further comprising a memory for storing the face image and the face part images acquired via a communications line, wherein the image obtaining unit is arranged to obtain the face image and the face part images from the memory.**5.** The information device according to any of the preceding claims, further comprising:

a digital camera for acquiring the face image; and
a memory for storing the face part images acquired via a communications line,

wherein the image obtaining unit is arranged to obtain the face image from the digital camera and the face part images from the memory.

6. The information device according to any of claims 1 to 4, further comprising:

a digital camera for acquiring the face part images; and
a memory for storing the face image acquired via a communications line,

wherein the image obtaining unit is arranged to obtain the face part image from the digital camera and the face image from the memory.

7. The information device according to any of the pre-

ceding claims, wherein the face part images are images of eyes, nose, and mouth.

8. The information device according to any of the preceding claims, further comprising an operating unit with which an operator can select one facial expression from among a plurality of facial expressions, wherein the expression determining unit is arranged to determine the selected facial expression as the facial expression.**9.** The information device according to any of the preceding claims, further comprising:

a receiving unit for receiving a telephone call; a number obtaining unit for acquiring a telephone number of the telephone call; a memory for storing face images and face part images in correlation with telephone numbers; and
a display unit for displaying the combined face image,

wherein the expression determining unit is arranged to determine the facial expression based on a predetermined condition, and

the image combining unit is arranged to combine the face image and the face part images corresponding to the facial expression and corresponding to the telephone number to obtain the combined face image.

10. The information device according to claim 9, wherein the predetermined condition is a number of telephone calls that were not attended in a predetermined period.**11.** The information device according to claim 10, wherein the predetermined period is two hours.**12.** The information device according to any of the preceding claims, further comprising a display unit for displaying the face image, the face part images, or the combined face image.**13.** An information device comprising:

an image obtaining unit that is arranged to obtain a first face image and a second face image; a method determining unit that is arranged to determine a method for combining; and
an image combining unit that is arranged to combine the first face image and the second face image based on the thus determined method for combining to obtain a combined face image.

14. The information device according to claim 13, fur-

- ther comprising a communications unit for transmitting the first face image, the second face image, or the combined face image to another information device.
15. The information device according to claim 13 or 14, further comprising a digital camera for acquiring the first face image and the second face image, wherein the image obtaining unit is arranged to obtain the first face image and the second face image acquired by the digital camera.
16. The information device according to any of claims 13 to 15, further comprising a memory for storing the first face image and the second face image acquired via a communications line, wherein the image obtaining unit is arranged to obtain the first face image and the second face image from the memory.
17. The information device according to any of claims 13 to 16, further comprising:
- a digital camera for acquiring the first face image; and
 - a memory for storing the second face image acquired via a communications line,
- wherein the image obtaining unit is arranged to obtain the first face image from the digital camera and the second face image from the memory.
18. The information device according any of claims 13 to 17, further comprising an operating unit with which an operator can select the first face image and the second face image from among a plurality of face images.
19. The information device according to any of claims 13 to 18, wherein the method for combining is one or more selected from the group consisting of
- using eyes and mouth of the first face image and using a total face and other face parts of the second face image,
 - using parts of the first face image and the second face image based on generation of random numbers,
 - using a position information of the total face and the face parts of the first face image, and using shapes of the total face and the face parts of the second face image, and
 - using an intermediate value of the face parts of the first face image and the second face image.
20. The information device according to any of claims 13 to 19, further comprising a display unit for displaying the first face image, the second face image, or the combined face image.

21. An information device comprising:

an image obtaining unit that is arranged to obtain a first face image and a second face image; a determining unit that is arranged to determine a similarity between the first face image and the second face image and a relationship between the persons of the first face image and the second face image determined from the similarity; and a display unit for displaying the similarity, the relationship or both the similarity and the relationship.

22. A computer program containing instructions which, when executed on a computer, cause the computer to perform:

acquiring a face image and a plurality of face part images corresponding to facial expressions; determining a facial expression; combining the face image and the face part images corresponding to the facial expression to obtain a combined face image; and displaying the combined face image.

23. A computer program containing instructions which, when executed on a computer, cause the computer to perform:

acquiring a first face image and a second face image; determining a method for combining; combining the first face image and the second face image based on the method for combining to obtain a combined face image; and displaying the combined face image.

24. A computer program containing instructions which, when executed on a computer, cause the computer to perform:

obtaining a first face image and a second face image; determining a similarity between the first face image and the second face image and a relationship between the persons of the first face image and the second face image determined from the similarity; and displaying the similarity, the relationship or both the similarity and the relationship.

25. A computer readable storage medium having stored thereon a computer program according to any of claims 22 to 24.

FIG.1




FIG.2A

ORIGINAL IMAGE



FIG.2B

EXTRACTION OF FACE PARTS



FIG.2C

PREPARATION OF A PORTRAIT



FIG.3




FIG.4

TELEPHONE NUMBER.	PORTRAIT	TOTAL FACE POSITION	FACE PART/POSITION			COLOR	
			EYES	MOUTH	TOTAL FACE	HAIR
XXXXXXXX	XXXXXX	XX	X	X	XX	X
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮

FIG.5

EXPRESSION ASSIGNMENT INFORMATION	FACE PART		
	EYES	MOUTH
XXXXXXXX	XXXXXXXX	XXXXXXXX
⋮	⋮	⋮	⋮

FIG.6

TELEPHONE NUMBER	CALL RECEPTION TIME	ABSENCE OR RESPONSE
XXXXXXXX	XXXXXXXX	XXXXXXXX
⋮	⋮	⋮

FIG.7

NUMBER OF TIMES OF ABSENCE	EXPRESSION ASSIGNMENT INFORMATION
XXXXXXXX	XXXXXXXX
⋮	⋮

FIG.8




FIG.9






FIG.10

ORIGINAL PORTRAIT



EXPRESSIONS
CHANGED

CHANGED PORTRAIT



FIG.11




FIG.12




FIG.13




FIG.14




FIG.15




FIG.16




FIG.17




FIG.18




FIG.19




FIG.20





FIG.21





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 330 124 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
05.11.2003 Bulletin 2003/45

(51) Int Cl.7: **H04N 7/14**

(43) Date of publication A2:
23.07.2003 Bulletin 2003/30

(21) Application number: **03250305.4**

(22) Date of filing: **17.01.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT SE SI SK TR**
Designated Extension States:
AL LT LV MK RO

- Yamamoto, Mitsuhiko, c/o Fujitsu Limited
Kawasaki-shi, Kanagawa 211-8588 (JP)
- Kikuchi, Misao, c/o Fujitsu Limited
Kawasaki-shi, Kanagawa 211-8588 (JP)
- Kage, Hiroshi, c/o Mitsubishi Denki KK
Tokyo 100-8310 (JP)
- Takeda, Akihiro, c/o Mitsubishi Denki KK
Tokyo 100-8310 (JP)
- Tanaka, Kenichi, c/o Mitsubishi Denki KK
Tokyo 100-8310 (JP)

(30) Priority: **17.01.2002 JP 2002008193**

(71) Applicants:
• **FUJITSU LIMITED**
Kawasaki-shi, Kanagawa 211-8588 (JP)
• **MITSUBISHI DENKI KABUSHIKI KAISHA**
Tokyo 100-8310 (JP)


(74) Representative: **Williams, Michael Ian**
Haseltine Lake
Imperial House
15-19 Kingsway
London WC2B 6UD (GB)

(72) Inventors:
• **Taniguchi, Shigeki, c/o Fujitsu Limited**
Kawasaki-shi, Kanagawa 211-8588 (JP)

(54) **Information device and computer product**

(57) A transmission-side cellular phone (20) sends, via a mail server (40), to a reception-side cellular phone (30), a face image and its attribute information as an attachment to an email. The reception-side cellular phone (30) extracts the face image from the email, selects face part images from among a plurality of face

part images stored in the face part storing section, combines the face image and the selected face parts, and displays the combined image. The reception-side cellular phone (30) selects the face part images based on, for example, a number of times a telephone call from a person was not attended in a predetermined period.





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 25 0305

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	GB 2 362 534 A (MOTOROLA ISRAEL LTD) 21 November 2001 (2001-11-21) * page 7, line 2 - page 8, line 25 * * page 9, line 22 - page 10, line 3 * * figures 1,2 *	1-4,6, 12-17, 20-24	H04N7/14
A	DE 100 03 632 A (AKIYAMA YOSHIRO) 31 August 2000 (2000-08-31) * page 3, column 3, line 6 - column 4, line 52 *	1,7-9	
A	EP 0 989 750 A (SIEMENS AG) 29 March 2000 (2000-03-29) * page 3, column 3, line 17 - column 4, line 28 *	9-11	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7) H04N G10L
Place of search THE HAGUE		Date of completion of the search 16 September 2003	Examiner Van der Zaal, R
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.02.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 25 0305

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-09-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2362534 A	21-11-2001	NONE	
DE 10003632 A	31-08-2000	DE 10003632 A1	31-08-2000
		FI 20000161 A	24-08-2000
		FR 2790166 A1	25-08-2000
		GB 2351638 A	03-01-2001
		IT MI20000045 A1	17-07-2001
		SE 0000283 A	25-08-2000
EP 0989750 A	29-03-2000	EP 0989750 A2	29-03-2000

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)

Scanned: 11/11/10
To Sweden: